


Part number

CX 25 IF



Brief description:

female insert, 25 poles, crimp connections, 4A 50V, 3, for 5A female contacts, 1 module, modular units series MIXO

Product description		Approvals / Standards	
Model	female insert	Reference standard	EN 61984:2009-06
Version	Crimp connection	Quality mark	 EAC
Product type	for 5A female contacts	Conformity	Not applicable
Family	MIXO series, customizable inserts	General ordering information	
Size	1 module	EAN13 code	8015747148313
N. of poles	25 poles	Tariff number	85369095
Technical data		Packaging Information	
Current	4 A (A.C. and D.C.)	Packaging length	180,00 mm
Voltage	50 V	Packaging height	130,00 mm
Pollution degree	3	Packaging width	150,00 mm
Operating temperature range (min, max)	-40°C ... +125°C	Packaging weight	2,00 kg
IP degree of protection	IP20 without enclosure, IP65/IP66/IP68/IP69 with enclosure	Packaging volume	3,51 dm ³
Further technical details		Packaging description	Carton box
Characteristics according to EN 61984	5A 50V 10A 3	Packaging quantity	60 Pcs
Insulation resistance	≥ 10 GΩ	Packaging EAN code	8015747221351
Rated voltage according to UL/CSA	50V	Sub-packaging length	35,00 mm
UL 94 flammability rating	V-0	Sub-packaging height	40,00 mm
Weight	9,00 g	Sub-packaging width	155,00 mm
		Sub-packaging weight	0,33 kg
		Sub-packaging volume	0,22 dm ³
		Sub-packaging description	Carton tray
		Sub-packaging quantity	10 Pcs
		Sub-packaging EAN barcode	8015747148337

Part number

CX 25 IF



Notes

Inserts CX 25 IF/M

- characteristics according to EN 61984:
4A 50V 0.8kV 3
4A 160V 2.5kV 2
- insulation resistance: > 10 GOhm
- ambient temperature limit: -40 °C ... +125 °C
- are made of self-extinguishing thermoplastic resin
UL 94 V0
- mechanical life: > 500 cycles
- for crimp contacts CI series using:
CIPZ D crimping tool
CITP D turret head
CIES insertion / removal tool
- we recommend the use of CRF / CRM code pins
- 1 frame slot

the modular inserts must be installed in suitable frames which in turn are installed in traditional housings or COB panel support
