

Part number

CX 01 9VM



Brief description:

male insert, module adapter for 1 D-SUB connector, 5A 50V, 0,8kV, 3, male insert with D-SUB connector and shield, 1 module, modular units series MIXO

Product description	
Model	male insert
Version	module adapter for 1 D-SUB connector
Product type	male insert with D-SUB connector and shield
Family	MIXO series, customizable inserts
Size	1 module
N. of poles	9 poles
Technical data	
Current	5 A (A.C. and D.C.)
Voltage	50 V
Rated impulse withstand voltage	0,8kV
Pollution degree	3
Operating temperature range (min, max)	-40°C ... +125°C
IP degree of protection	IP20 without enclosure, IP65/IP66/IP68/IP69 with enclosure
Further technical details	
Characteristics according to EN 61984	5A 50V 0.8kV 3
Insulation resistance	≥ 5 GΩ
Rated voltage according to UL/CSA	600V
UL 94 flammability rating	V-0
Weight	20,00 g

Approvals / Standards	
Reference standard	EN 61984:2009-06
Conformity	Not applicable
General ordering information	
EAN13 code	8015747095846
Tariff number	85369095
Packaging Information	
Packaging length	112,00 mm
Packaging height	95,00 mm
Packaging width	117,00 mm
Packaging weight	0,20 kg
Packaging volume	1,24 dm³
Packaging description	Carton box
Packaging quantity	10 Pcs
Packaging EAN code	8015747095853
Sub-packaging weight	0,02 kg
Sub-packaging description	Plastic bag
Sub-packaging quantity	1 Pcs
Sub-packaging EAN barcode	8015747095860

Part number

CX 01 9VM



Notes

MIXO D-SUB inserts

- characteristics according to EN 61984:
5A 50V 0,8kV 3
- for crimp 5A contacts CI series using:
CIPZ D crimping tool
CIVTP D turret head
CIVES insertion / removal tool
- footprint 1 module
- we recommend the use of CRF CX / CRM CX code pins
- enclosures: housings or high construction hoods

the modular inserts must be installed in suitable frames which in turn are installed in traditional housings or COB panel support
