

## PRICE HAMMER !!! - Nickel plated Brass & Polyamid 6

### Characteristics:

- Standard cable gland in nickel plated brass suitable for most applications
- FEATURES : Good clamping range, halogen free, sulphur free, phosphorus free, UL 94 V2 flame retardancy, high mechanical strength, easy installation, high strain relief
- APPLICATIONS: MACHINE BUILDINGS, AUTOMATION SYSTEMS, AUTOMOTIVE (WIRE HARNESS), SOLAR SYSTEMS, CONSTRUCTION, CCTV, MARINE , SHIPYARD, ROBOT INDUSTRY.

### Technical information:

Material	: Nickel plated brass	: Polyamid 6
Standards	: CE, GOST,ROHS, TUV	: EN 62444 / TS EN 50262
Temperature range	: -40°C to 100°C	: -20°C / +100°C (static) , : -30°C / +150°C ( dynamic )
Protection Class	: IP 68	: IP 68
Inside	: Polyamid 6	: Polyamid 6
Sealing ring	: Chloroprene, NBR	: Chloroprene
Flammability		: UL94 V2



### CABLE GLAND Metal

Type.no Brass	Type.no Brass long thread	Thread	Cable Ø mm	Thread length mm	Thread length long mm	Key width	Quantity [pieces]
TMR-0S	TMRU-0S	M12x1,5	3,0 - 6,5	6	12	14	50
TMR-01	TMRU-01	M16x1,5	4,0 - 8,0	7	12	17	50
TMR-01S	-	M16x1,5	5,0 - 10,0	7	-	20	50
TMR-02	TMRU-02	M20x1,5	6,0 - 12,0	8	12	22	50
TMR-03	TMRU-03	M25x1,5	10,0 - 14,0	8	12	24	25
TMR-03/1	-	M25x1,5	13,0 - 18,0	8	-	30	25
TMR-04	TMRU-04	M32x1,5	13,0 - 18,0	9	15	30	25
TMR-04/1	-	M32x1,5	18,0 - 25,0	8	-	40	25
TMR-05	TMRU-05	M40x1,5	18,0 - 25,0	9	15	40	20
TMR-06	TMRU-06	M50x1,5	22,0 - 32,0	9	15	50	15
TMR-06S	-	M50x1,5	29,0 - 40,0	9	-	57	10
TMR-07	TMRU-07	M63x1,5	34,0 - 44,0	14	18	64	12
TMR-07S	-	M63x1,5	37,0 - 53,0	10	-	75	10

### CABLE GLAND Plastic

Type.no PA6 Gray (RAL 7035)	Type.no PA6 Black (RAL 9005)	Thread	Cable Ø mm	Thread length mm		Key width	Quantity [pieces]
TMO-0SA.G	TMO-0SS	M12x1,5	3,0 - 6,5	8		15	100
TMO-01A.G	TMO-01S	M16x1,5	5,0 - 10,0	10		22	50
TMO-02A.G	TMO-02S	M20x1,5	6,0 - 12,0	10		24	50
TMO-05A.G	TMO-05S	M25x1,5	13,0 - 18,0	10		33	25
TMO-07A.G	TMO-07S	M32x1,5	18,0 - 25,0	18		42	20
TMO-08A.G	TMO-08S	M40x1,5	22,0 - 32,0	18		53	10
TMO-09A.G	TMO-09S	M50x1,5	30,0 - 38,0	18		60	10
TMO-10A.G	TMO-10S	M63x1,5	34,0 - 44,0	18		65	10

PG threads in metal and plastic are available on request